IN THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of the claims in the application:

- 1. (**Currently amended**) An ATV comprising: a frame;
 - at least three wheels suspended from the frame, at least one of which is a front wheel and at least one of which is a rear wheel, the front wheel defining a front axis and the rear wheel defining a rear axis, the front axis and the rear axis defining a wheelbase of 52 to 72inches;
 - a power unit mounted on the frame for driving at least one of the wheels;
 - a straddle-type seat supported by the frame including a main seat portion for a driver and a secondary seat portion, rearward of <u>and adjacent to</u> the main portion, for a passenger;
 - a steering member connected to the frame for steering at least one of the wheels; and at least one passenger grab handle.
- (Original) The ATV of claim 1, wherein:
 the at least three wheels comprise only four wheels, two of which are front wheels
 and two of which are rear wheels;
 each of the wheels includes an ATV type a tire; and
 the steering member comprises handlebars.
- 3. (**Original**) The ATV of claim 2, wherein the wheelbase is between 55 and 65 inches.
- 4. (**Original**) The ATV of claim 2, wherein the wheelbase is between 56 and 64 inches.
- 5. (**Original**) The ATV of claim 2, further comprising a right passenger grab handle and left passenger grab handle.
- 6. (**Original**) The ATV of claim 5, wherein the right passenger grab handle and left passenger grab handle do not extend above the secondary seat portion by more than 4 inches.
- 7. (**Original**) The ATV of claim 2, wherein there are two passenger grab handles disposed on the right and left side of the secondary supporting portion, the grab handles not extending above the secondary supporting portion by more than 3 inches.
- 8. (**Original**) The ATV of claim 7, wherein the secondary supporting range includes a secondary supporting portion, and wherein the grab handle do not extend above the secondary supporting range by more than 2 inches.
- 9. (**Original**) The ATV of claim 2, wherein the grab handle is mounted to the ATV separately from the secondary seat portion.
- 10. (**Original**) The ATV of claim 2, wherein the grab handle is longitudinally aligned with the secondary seat portion.
- 11. (**Original**) The ATV of claim 2, wherein the grab handle is disposed laterally outwardly from the secondary seat portion.

- 12. (**Original**) The ATV of claim 11, further comprising a rear rack mounted to a rearward portion of the ATV, wherein the grab handle is attached to the rear rack.
- 13. (**Original**) The ATV of claim 11, further comprising a rear rack mounted to a rearward portion of the ATV, wherein the grab handle extends forwardly from the rear rack.
- 14. (**Original**) The ATV of claim 11, further comprising a rear rack mounted to a rearward portion of the ATV, wherein the rear rack supports the grab handle.
- 15. (**Original**) The ATV of claim 11, further comprising a rear rack mounted to a rearward portion of the ATV, wherein the rear rack extends laterally outwardly beyond the grab handle.
- 16. (**Original**) The ATV of claim 5, wherein the grab handles each comprise a ring-shaped portion.
- 17. (**Original**) The ATV of claim 16, wherein the ring-shaped portion extends generally horizontally.
- 18. (**Original**) The ATV of claim 16, wherein the grab handle further comprises gripping knobs disposed within the ring-shaped portions such that the ring shaped portions function as hand guards.
- 19. (**Original**) The ATV of claim 16, wherein the ring shaped portions of the grab handle is flexible.
- 20. (**Original**) The ATV of claim 5, wherein the grab handle comprises a resilient material.